

## Mounting Instructions Steering Reset (bottom mount)



### Content

2x ball joint with locking clip  
1x steering rod  
2x spring  
2x high polymer bushing  
1x reset bracket

2x button head screw M6x30  
4x nylon nut M6  
2x little washer 6  
1x mounting instructions

### required tools

1x torx key wrench T25  
1x spanner 10mm  
1x spanner 8mm  
1x hex key wrench 4mm  
1x hex key wrench 5mm

### Note

Mounting of this kit requires skill and dexterity.  
If it is too risky to you better let a specialist mount this kit for you.

### Dismanteling

- unbolt the tensioning screw (that with the plastic black or colored sleeves) between the head brackets in front of the black block of the pole
- unscrew the complete front axle
- unscrew the old steering rod

### Mounting of the steering reset kit

- remove the button head screws from the pre-assembled steering reset kit (fig. 1)
- remove the nuts from both ball joints, but not the washers
- place the pre-assembled steering rod between the steering brackets so that the bores of the reset bracket correspond to the axle ones (fig. 2)
- insert the ball studs into the belonging bottom bores of the steering brackets (the washers must be placed between the ball studs and the steering brackets)
- screw tight the first ball stud and then press the other one against the steering bracket
- check the steering brackets being parallel! If not, pull out the loose ball stud and correct the length of the steering rod by full turns of the ball stud until the length is ok
- screw tight the second ball stud.
- slide the button head screws head on through the front axle and screw tight the nuts in the back of the reset bracket
- mount the completed front axle to the head brackets. Tighten the screws well!
- tighten the tension screw between the head brackets.
- make sure the pole turns down as easy as before. If required, unbolt the tensioning screw a bit

### Checking

- check the turning ability of the wheelz left and right
- the wheelz must return smooth and automatically to straight position




fig. 1



fig. 2

**Ciro Shop - Straka.DES - Markt 2 - 08340 Schwarzenberg - Germany**  
**shop@ciro.de - fax: ++ (0)3774 - 17643817**

© Straka.DES. State 01.01.17